



Colorcoat® SDP 50 Matt Standard Colours



TSNBlack Matt



TSNDark Grey Matt



TSNLight Grey Matt



TSNBrown Matt



TSNTerracotta Matt



TSNRed Matt

Printed colours are for guidance only.

Please request a sample from us to assess the exact colour and texture before specifying.

Colorcoat® SDP 50 Matt is a durable prepainted steel for roof and walls. An attractive low gloss and textured product with a long guarantee and excellent colour stability.

- Developed for roof applications, but equally suitable for walls.
- 50µm low gloss textured coating for improved scratch and abrasion resistance combined with excellent corrosion protection.
- Better grip for the contractor and engineer who walks on the roofs.
- Colorcoat SDP 50 Matt complies with the recommendation of IFBS, to specify a coating thickness of at least 45µm for roofs used for services or solar installations.
- Up to 25 years performance guarantee from Tata Steel. No registration required. The guarantee also applies when solar panels are installed.
- Ruv5 and RC5+
- Low carbon footprint, a third party verified EPD is available.
- BES 6001 certified. Fully REACH compliant. Available with Zeremis® Carbon Light.
- Available in most popular roofing colours.

Wide range of colours

Colorcoat SDP 50 Matt is available in a variety of standard roof and wall colours. Non-standard colours are also available upon request. Production hand samples are available for the best assessment of texture, colour and effect. To ensure consistency of colour on a single surface, it is recommended to use material from the same production batch.

Tata Steel Performance Guarantee

- Up to 25 years guarantee
- Full coverage during entire period
- Guarantee also applies if solar modules are installed
- The guarantee starts automatically. No further action required
- Full coverage without any registration within Europe

The actual guarantee period and conditions are stated on the guarantee document.

Typical Properties

Colorcoat® SDP 50 Matt		Test norm
Nominal organic coating thickness	50µm	EN 13523 - 1
Gloss level (60°)	0 – 5%	EN 13523 - 2
Scratch resistance (g)	>3000	EN 13523 - 12
Flexibility: Minimal bending radius	1T @ 16°C	EN 13523 - 7
Adhesion	≤ 1T	EN 13523 - 7
Corrosion resistance		
Salt spray test	1000 h	EN 13523 - 8
Condensation test	1500 h	EN 13523 - 26
Corrosion resistance class	RC5+	EN 10169
UV resistance	Ruv5	EN 10169
Reaction to fire, Class*	A1	EN 13501 - 1

Notes

The figures contained in this table are typical properties of the topcoat and do not constitute a specification.

Zinc weight of Z275 gr/m² or ZM140 gr/m² (MagiZinc) applies.

* Fire rating depends on thickness. Please contact Tata Steel for more information.

Sales Contact Details:

Tata Steel Nederland

Wenckenbackstraat 1
1951 JZ Velsen-Noord
The Netherlands

[E: Connect.Colors@tatasteelurope.com](mailto:Connect.Colors@tatasteelurope.com)

Tata Steel Maubeuge SAS,

22, Av. Jean de Beco
59720 Louvroil
France

[E: Connect.Colors@tatasteelurope.com](mailto:Connect.Colors@tatasteelurope.com)

www.tatasteelnederland.com

Trademarks of Tata Steel

Colorcoat®, MyriaPlus®, MagiZinc® and Zeremis® are trademarks of Tata Steel. While care has been taken to ensure that the information contained in this publication is accurate, neither Tata Steel, nor its subsidiaries, accept responsibility or liability for errors or for information which is found to be misleading. Before using products or services supplied or manufactured by Tata Steel and its subsidiaries, customers should satisfy themselves as to their suitability.

Tata Steel IJmuiden BV is registered in The Netherlands under number 34040331 at Wenckebackstaat 1, 1951 JZ Velsen-Noord, The Netherlands.

Tata Steel Maubeuge SAS is registered in France under number 445 720 295 RCS Valenciennes, at 22, Av. Jean de Beco, 59720 Louvroil, France.

Copyright 2024 Tata Steel
Language EN 0424